

## ORDERING INFORMATION

# SN-E□□H-CM

Series name

Rated current

MODE(COMMON MODE)

### FEATURE

- Good attenuation characteristics high voltage impulse
- Suitable for the products that must conform to FCC, FTZ
- Low leakage

### APPLICATION

- Industrial equipments
- Personal computer & peripherals
- Digital equipments



## SN-P, M, E, SUP SPECIFICATIONS 1Ø



| MODEL       | RATED VOLTAGE (AC/DC) | RATED CURRENT | LEAKAGE CURRENT (60Hz) | TEMPERATURE RISE | OPERATING TEMPERATURE RANGE | APPROVAL   |
|-------------|-----------------------|---------------|------------------------|------------------|-----------------------------|------------|
| SN-02P      | 250V Max              | 2A            | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 | UL,C-UL,CE |
| SN-03P      | 250V Max              | 3A            | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 | UL,C-UL,CE |
| SN-06P      | 250V Max              | 6A            | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 | UL,C-UL,CE |
| SN-M1H-CM   | 250V Max              | 1A            | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 | UL,C-UL,CE |
| SN-M3H-CM   | 250V Max              | 3A            | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 | UL,C-UL,CE |
| SN-M6H-CM   | 250V Max              | 6A            | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 | UL,C-UL,CE |
| SN-E5H-CM   | 250V Max              | 5A            | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 | UL,C-UL,CE |
| SN-E6H-CM   | 250V Max              | 6A            | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 | UL,C-UL,CE |
| SN-E10H-CM  | 250V Max              | 10A           | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 | UL,C-UL,CE |
| SN-E15H-CM  | 250V Max              | 15A           | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 | UL,C-UL,CE |
| SN-E20H-CM  | 250V Max              | 20A           | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 | UL,C-UL,CE |
| SUP-E30H-CM | 250V Max              | 30A           | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 |            |
| SUP-E40H-CM | 250V Max              | 40A           | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 |            |
| SUP-E50H-CM | 250V Max              | 50A           | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 |            |
| SUP-E60H-CM | 250V Max              | 60A           | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 |            |
| SUP-E70H-CM | 250V Max              | 70A           | 0.5mA Max              | 40°C Max         | -25 ~ +85°C                 |            |